

SUBMITTAL: MODEL CT FLUSH ACCESS PANELS

PAGE 1 OF 1

Model CT for Acoustic Tile or Drywall Ceilings :

Sound control and appearance are the important features of Model CT: When installed, indiscernible, yet keeping acoustical surfaces intact. A covering of acoustical tile or drywall is applied to the recessed door panels with exposure of only the narrow frame edges. Acoustical tile or drywall up to 1" thick is accommodated by the recessed panel. Adhesive mastic of adequate depth attaches the tile to the door and ensures that it is flush with adjoining tile field. A continuous hinge, located at the outside edge of the door ensures easy opening of the plaster or tile covered panel. Screwdriver operated cam locks are provided, the size of the door determining the number. If desired, a key-operated cylinder lock, in place of one cam lock can be furnished. Not to be used for suspended ceilings.

SPECIFICATIONS:

Door Panel: 18 gauge steel, recessed 1" for tile or drywall.

Frame: 16 gauge steel

Finish: White primer coat

Hinge: Continuous hinge mounted on the long side of oblong panels.

Lock: Flush screwdriver-operated steel cam standard.

Panel at right shown as partially-covered by acoustic tile



OPTIONAL FEATURES AT ADDITIONAL COST:

☐ Optional color Code: _____ - see catalog or [website](#)

W-White, **R**-Red, **BK**-Black, **S**-sand

FBK-Flat Black, **AB**-AMS Beige, **B**-Bronze

SB-SC Flat Beige, **SA** - Satin Aluminum

☐ (L) Cylinder lock installed

☐ (CT) Torx head cam

☐ (CA) Hex head cam

☐ (SHC) Spanner head cam

☐ Optional Door Panel Depth (1/4-1") _____ "

QTY	A MODEL SIZE	B OUTSIDE FRAME DIMENSIONS		SHIPPING WEIGHT APPROX.	LATCH (ES)
	WIDTH X HEIGHT	WIDTH	HEIGHT		
	12" X 12"	12 1/4 "	12 1/4 "	7 lbs	1
	12" X 24"	12 1/4 "	24 1/4 "	11 lbs	2
	18" X 18"	18 1/4 "	18 1/4 "	12 lbs	3
	22" X 30"	22 1/4 "	30 1/4 "	18 lbs	4
	24" X 24"	24 1/4 "	24 1/4 "	17 lbs	4
	24" X 36"	24 1/4 "	36 1/4 "	27 lbs	5

