



FD2L SERIES - 2 HOUR FIRE-RATED LAUNDRY OR GARBAGE CHUTE ACCESS DOOR

A Specialty two hour fire-rated door for laundry or garbage chute access. The wider 1-3/4" Flange covers opening edges and the handle provides easy access to the chute. Optional smoke gasket for garbage chute installations

Materials: Painted, galvanized steel or 304 stainless steel.

Frame: 16 ga (1.61mm) steel. Depth "D"= 2-3/4" (70mm)

Wall Trim: Width - 1-3/4" (45mm) with a 3/8" (9.52mm) return.

Door Panel: 18 ga (1.31mm) with 22 ga (0.85mm) liner

Insulation: The door panel contains 1-1/2" (38mm) of high temperature insulation material.

Finishes: The paint finish is an electrostatically applied rust inhibitive prime coat or a No. 4 polished stainless steel finish on exterior surface.

Hinges: The continuous stainless steel piano hinge is designed to secure the door panel and open to 180°. The hinge is placed on the long side of the door ("H" dimension) unless otherwise requested.

Panel Closer: Listed concealed door closure.

Latch: The standard factory installed latch is a non-locking "T" handle.

This model of wall and ceiling fire-rated panels is manufactured under the factory inspection service of Intertek Warnock Hersey) and have a label reading: "Listed access frame and insulated fire door assembly 2 hour fire rating. Vertical Installation only. Temperature rise maximum 139° C / 250° F at 30 minutes, 250° C / 450° F at 60 minutes."