

Larsen's fire blanket cabinets are all equipped with a 62" x 80" fire blanket fabricated of a rugged blend of reprocessed wool. These fire retardant blankets meet federal specification #CS-191-53. Larsen's fire blanket cabinets are available in the three following designs:

FB 68-6 SERIES: Fire blanket is attached to a roller and can be rapidly released by placing one's arm through the arm loop and turning into the blanket. This surface mounted unit is constructed of cold-rolled steel with a standard finish of red baked acrylic enamel, and as an option, the cabinet can be fabricated entirely of stainless steel (Model SS FB 68-6).

FB 1016 SERIES: Drop Type, surface mounted cabinet, constructed of cold-rolled steel with a red baked acrylic enamel finish. The folded blanket is always visible through the viewing knockout on the front and is quickly available by releasing the hinged bottom of the cabinet.

FB 3612 SERIES: Exclusive combination fire extinguisher and fire blanket cabinet, which is identical to the Architectural Series model 3612 (see Architectural Series) except for the blanket shelf located 9" down from the top of the cabinet, leaving 27" for the extinguisher height. Please consult Architectural Series for wall mounting, trim and door material, and appropriate door style options. The unit is also available with Gemini door styles (model G FB 3612 - Gemini Series), with "Fire Extinguisher" (vertical) and "Fire Blanket" (horizontal) lettering. If specified, "Fire Extinguisher" and "Fire Blanket" decals or die cut lettering are available with the appropriate door styles pictured on page 6. For steel door and trim units, white baked acrylic enamel is the standard color. Red is available if specified.



AL G FB 3612
 RED DOOR
 WHITE LETTERS



FB 1016



FB 3612

Model Number	Trim Style and Projection	Inside Box Dimensions H x W x D	Rough Opening H x W x D	Complies With ADA?
FB3612-R	Rec. 5/16	36 x 12 x 8	37 x 13 x 8 1/4	YES
FS FB3612-R	Rec. 5/16	36 x 12 x 8	38 1/8 x 14 1/8 x 9 1/8	YES
FB3612-RK	Semi-Rec. 1 1/4	36 x 12 x 8	37 x 13 x 7 1/4	YES
FS FB3612-RK	Semi-Rec. 1 1/4	36 x 12 x 8	38 1/8 x 14 1/8 x 8 1/8	YES
FB3612-RL	Semi-Rec. 2 1/2	36 x 12 x 8	37 x 13 x 6	YES
FS FB3612-RL	Semi-Rec. 2 1/2	36 x 12 x 8	38 1/8 x 14 1/8 x 7	YES
FB3612-RM	Semi-Rec. 4 1/2	36 x 12 x 8	37 x 13 x 4	■
FS FB3612-RM	Semi-Rec. 4 1/2	36 x 12 x 8	38 1/8 x 14 1/8 x 4 7/8	■
FB3612-RT	Trimless	36 x 12 x 8	--	YES
FB3612-SM	Surface Mtd.	39 1/2 x 15 1/2 x 8	--	■
FB3612-RA		36 x 12 x 8	37 x 13 x 4 1/2	■ ■
FS FB3612-RA	Semi-Rec. 4	36 x 12 x 8	38 1/2 x 14 1/2 x 5 1/2	■ ■ ■
FB68-6	Surface Mtd.	68 x 6 1/4 x 4	--	■
FB1016	Surface Mtd.	10 x 16 x 8	--	■

NOTE: "FS" models denote Larsen's "Flame-Shield" fire-rated cabinets. When specifying Larsen's "Flame Shield" fire-rated cabinet option for the Fire Blanket Cabinets, refer to the dimension chart above and select from the models with an "FS" prefix. Click here for complete details of the "Flame-Shield" option.

- To comply with ADA wall projection guidelines, this cabinet must be mounted with its leading edge at or below 27" from the finished floor.
- ■ To comply with ADA wall projection guidelines, this cabinet must be specified with Larsen's recessed handle.