

PROJECT: \_\_\_\_\_  
MODEL NUMBER: \_\_\_\_\_  
ARCHITECT: \_\_\_\_\_  
DATE: \_\_\_\_\_

LOCATION: \_\_\_\_\_  
QUANTITY: \_\_\_\_\_  
CONTRACTOR: \_\_\_\_\_  
DISTRIBUTOR: \_\_\_\_\_

**PW SERIES-Pressurized Water**

This unit is ideally suited for all industrial and commercial applications, where easy to use, positive on-off operation is important. Water is used as the extinguishing agent, making it highly effective on deep seated Class A fires. (Shipped empty.)

**WC SERIES-Wet Chemical**

Wet Chemical units are designed specifically for kitchen grease fire hazards and meet the new K class listing now required for all extinguishers installed in restaurant kitchens. They contain a special potassium acetate based, low PH agent, which leaves no chemical residue to clean up. The spray applicator wand keeps the operator at a safe distance from the fire. Larger 2-1/2 gallon unit with identical U.L. rating is available. (shipped charged)

**WM SERIES-Water Mist**

This unit is designated for use wherever there is a Class A hazard near electrical equipment and the environment is of paramount concern. The extinguishing agent is de-ionized water, and the wand provides greatest operator safety. There is no risk of electrical conductivity or thermal or static shock. Ideal for use in health care, data processing, telecommunication, and clean room facilities. (Shipped empty)



PW2½ & WM2½



WC2½ & WC-6L

MODEL NUMBER	NOMINAL CAPACITY	SHIPPING WEIGHT	CYLINDER DIAMETER	OVERALL HEIGHT	OVERALL WIDTH	UL RATING	STANDARD BRACKET*	OPTIONAL BRACKET*
PW2½	2½ gal.	7½ lbs.	7 in.	24½ in.	9 in.	2A	1007	B1, 864
WC-6L	6 liters	23 lbs.	7 in.	19 in.	9 in.	2A:K	1007	B1
WC2½	2½ gal.	34 lbs.	7 in.	24½ in.	9 in.	2A:K	1007	864
WM2½	2½ gal.	9 lbs.	7 in.	26 in.	11 in.	2A:C	14315	864

**CD SERIES---Carbon Dioxide**

These units contain liquid carbon dioxide under pressure. It is discharged as a white cloud of "snow," which effectively smothers a fire. Carbon dioxide is a clean, non-conductor of electricity for Class B and C fires.

MODEL NUMBER	NORMAL CAPACITY	SHIPPING WEIGHT	CYLINDER DIAMETER	OVERALL HEIGHT	OVERALL WIDTH	UL RATING	STANDARD BRACKET*	OPTIONAL BRACKET*
CD5	5 lbs.	14 lbs.	5¼in.	17¾ in.	8¼ in.	5-B:C	546	862
CD10	10 lbs.	28¼ lbs.	7 in.	24 in.	12 in.	10:B:C	575	N/A
CD15	15 lbs.	37¾ lbs.	7 in.	30 in.	12 in.	10:B:C	575	864
CD20	20 lbs.	50¾ lbs.	8 in.	30 in.	13 in.	10:B:C	577	864


All carbon dioxide units feature:

- O-ring seal, straight thread brass valve-fits all size
- Absolutely rust free aluminum cylinders
- Up to 30% lighter




□ CD5 □ CD10 □ CD15 □ CD20

**STANDARD BRACKETS\***



**OPTIONAL BRACKETS\***



**\*NOTE:** Standard brackets are included with all extinguishers at no additional cost. If specified, optional brackets are only available at additional cost. All of the above brackets are designed to accommodate Larsen's extinguishers. While most comparably sized extinguishers usually will function with the above brackets, Larsen's cannot assume responsibility for variations in cylinder dimensions among various extinguisher suppliers.

**LARSEN'S MANUFACTURING COMPANY**  
7421 Commerce Lane N.E., Mpls, MN 55432  
Phone: (763) 571-1181 FAX: (763) 571-6900  
[www.larsensmfg.com](http://www.larsensmfg.com)

**FLORIDA DIVISION:**  
3130 N.W. 17<sup>th</sup> Street, Ft. Lauderdale, FL 33311  
Phone: (954) 486-3325 FAX: (954) 486-3352

©2011 Larsen's Mfg. Co.