


PROJECT: \_\_\_\_\_  
MODEL NUMBER: \_\_\_\_\_  
ARCHITECT: \_\_\_\_\_  
DATE: \_\_\_\_\_

LOCATION: \_\_\_\_\_  
QUANTITY: \_\_\_\_\_  
CONTRACTOR: \_\_\_\_\_  
DISTRIBUTOR: \_\_\_\_\_




☐ **RECESSED HANDLE (Required only for 4" return trims when ADA wall projection compliance is necessary.)**

**SPECIFICATIONS:**  
"GEMINI" donates a frameless acrylic door, with color and design options as outlined below. The door is constructed of 1/4" thick smooth or textured acrylic. If lettering is specified, the design is placed on the back side of door to prevent damage. The Larsen-Loc® is available with all door styles. All doors have a satin finish pull handle with a self-adjusting roller catch; and continuous piano hinge constructed of material, which matches the trim.

**BOX SPECIFICATION:**  
All recessed and semi-recessed cabinets and surface-mounted steel cabinets have a heavy gauge, white baked enamel box. Surface-mounted cabinets with aluminum trim have a box constructed entirely of clear or color anodized aluminum. Surface-mounted cabinets with stainless steel door and trim have a box constructed entirely of 304 stainless steel with a #4 finish.

**TRIM SPECIFICATION:**  
Steel trims are one piece, constructed of heavy gauge, cold-rolled steel with a standard finish of white baked enamel, which can be used as either a finish or prime coat. Aluminum trims are constructed of extruded aluminum with satin anodized finish. Clear anodized is standard, and a wide selection of optional color anodized finishes is available. All trim corners are mitered. To specify aluminum trim, use the prefix "AL" before the cabinet model number. Stainless steel trims are one piece, constructed of heavy gauge, #4 finish, 304 stainless steel. To specify stainless steel trim, use the prefix "SS" before the cabinet model number.

(SEE BACK OF THIS SHEET OR ATTACHED SHEET FOR DIMENSIONS & DOOR STYLES)



† Trimless cabinets must be installed before the drywall because their plaster stops must be behind the drywall. Trimless cabinets are not recommended for block wall installation.


**LARSEN'S MANUFACTURING COMPANY - www.larsensmfg.com**  
7421 Commerce Lane N.E., Minneapolis, MN 55432 Phone: (763) 571-1181 FAX: (763) 571-6900  
**FLORIDA DIVISION:** 3130 N.W. 17<sup>th</sup> Street, Ft. Lauderdale, FL 33311 Phone: (954) 486-3325 FAX: (954) 486-3352  
©2011 Larsen's Mfg. Co.

CABINET DIMENSIONS - GEMINI SERIES

Model Number	Trim Style and Projection	Inside Box Dimensions			Outside Trim Dimensions**		Rough Opening***			Recommended Extinguisher Capacity
		Height	Width	Depth	Height	Width	Height	Width	Depth	
G2409-R1	Rec. 5/16"	24"	9½"	5"	27½"	13"	25"	10½"	5¼"	MP2½, MP5, MP5-A DC2½, DC5, HT2½, HT5
G2409-5R	Semi-Rec. 1½"	24"	9½"	5"	27½"	13"	25"	10½"	4"	
G2409-R3	Semi-Rec. 2½"	24"	9½"	5"	27½"	13"	25"	10½"	3"	
G2409-R2	Rec. 5/16"	24"	9½"	6"	27½"	13"	25"	10½"	6¼"	MP2½, MP5, MP5-A, DC2½, DC5, MP6, MP10, DC6,DC10,CD5, HT2½, HT5
G2409-R7	Semi-Rec. 1½"	24"	9½"	6"	27½"	13"	25"	10½"	5"	
G2409-6R	Semi-Rec. 2½"	24"	9½"	6"	27½"	13"	25"	10½"	4"	
G2409-RM	Semi-Rec. 4½"	24"	9½"	6"	27½"	13"	25"	10½"	2"	
G2409-RT	Trimless	24"	9½"	6"	-	-	†	†	6½"	
G2409-R4	Semi-Rec. 3½"	24"	9½"	6"	27½"	13"	25"	10½"	3"	
G2409-SM	Surface Mounted	27½"	13"	6"	27½"	13"	-	-	-	
G2409-RA	Semi-Rec. 4"	24"	9½"	6"	27½"	13"	25"	10½"	2½"	
* Depth of these cabinets is 4-3/4" when supplied with aluminum door and frame. The ALG2409-5R has a 1-1/4" square trim.										
G2712-R	Rec. 5/16"	27"	12"	8"	30½"	15½"	28"	13"	8¼"	All of Above, PW2½, MP20 DC20, CD10 WC-6L, HT11, HT15½ WC2½, WM2½
G2712-RK	Semi-Rec. 1¼"	27"	12"	8"	30½"	15½"	28"	13"	7¼"	
G2712-RL	Semi-Rec. 2½"	27"	12"	8"	30½"	15½"	28"	13"	6"	
G2712-RM	Semi-Rec. 4½"	27"	12"	8"	30½"	15½"	28"	13"	4"	
G2712-RT	Trimless	27"	12"	8"	-	†	†	†	8½"	
G2712-SM	Surface Mounted	30½"	15½"	8½"	30½"	15½"	-	-	-	
G2712-RA	Semi-Rec. 4"	27"	12"	8"	30½"	15½"	28"	13"	4½"	
G2720-R	Rec. 5/16"	27"	20"	8"	30½"	23½"	28"	21"	8¼"	Two Each of the Listed PW2½, MP10, DC10, MP20, DC20 CD5, CD10, WC-6L HT11, HT15½ WC2½, WM2½
G2720-RK	Semi-Rec. 1¼"	27"	20"	8"	30½"	23½"	28"	21"	7¼"	
G2720-RL	Semi-Rec. 2½"	27"	20"	8"	30½"	23½"	28"	21"	6"	
G2720-RM	Semi-Rec. 4½"	27"	20"	8"	30½"	23½"	28"	21"	4"	
G2720-RT	Trimless	27"	20"	8"	-	-	†	†	8½"	
G2720-SM	Surface Mounted	30½"	23½"	8½"	30½"	23½"	-	-	-	
G2720-RA	Semi-Rec. 4"	27"	20"	8"	30½"	23½"	28"	21"	4½"	
G3012-R	Rec. 5/16"	30"	12"	8"	33½"	15½"	31"	13"	8¼"	Same as G2712
G3012-RK	Semi-Rec. 1¼"	30"	12"	8"	33½"	15½"	31"	13"	7¼"	
G3012-RL	Semi-Rec. 2½"	30"	12"	8"	33½"	15½"	31"	13"	6"	
G3012-RM	Semi-Rec. 4½"	30"	12"	8"	33½"	15½"	31"	13"	4"	
G3012-RT	Trimless	30"	12"	8"	-	-	†	†	8½"	
G3012-SM	Surface Mounted	33½"	15½"	8½"	33½"	15½"	-	-	-	
G3012-RA	Semi-Rec. 4"	30"	12"	8"	33½"	15½"	31"	13"	4-1/2"	
G3612-R	Rec. 5/16"	36"	12"	8"	39½"	15½"	37"	13"	8¼"	Same as G2712
G3612-RK	Semi-Rec. 1¼"	36"	12"	8"	39½"	15½"	37"	13"	7¼"	
G3612-RL	Semi-Rec. 2½"	36"	12"	8"	39½"	15½"	37"	13"	6"	
G3612-RM	Semi-Rec. 4½"	36"	12"	8"	39½"	15½"	37"	13"	4"	
G3612-RT	Trimless	36"	12"	8"	-	-	†	†	8½"	
G3612-SM	Surface Mounted	39½"	15½"	8½"	39½"	15½"	-	-	-	
G3612-RA	Semi-Rec. 4"	36"	12"	8"	39½"	15½"	37"	13"	4½"	
G3216-R	Rec. 5/16"	32"	16"	8"	35½"	19½"	33"	17"	8¼"	PW2½, MP20, DC20,CD10, CD15 WM2½ WC2½
G3216-RK	Semi-Rec. 1¼"	32"	16"	8"	35½"	19½"	33"	17"	7¼"	
G3216-RL	Semi-Rec. 2½"	32"	16"	8"	35½"	19½"	33"	17"	6"	
G3216-RM	Semi-Rec. 4½"	32"	16"	8"	35½"	19½"	33"	17"	4"	
G3216-RT	Trimless	32"	16"	8"	-	-	†	†	8½"	
G3216-SM	Surface Mounted	35½"	19½"	8½"	35½"	19½"	-	-	-	
G3216-RA	Semi-Rec. 4"	32"	16"	8"	35½"	19½"	33"	17"	4½"	

† Trimless cabinets must be installed before the drywall because their plaster stops must be behind the drywall. Trimless cabinets are not recommended for block wall installation.

\*\* Deduct ¾" from HxW dimensions for cabinets with aluminum trim.  
\*\*\* Rough openings are larger for fire-rated cabinets. Please refer to Fire-rated Extinguisher Cabinet Submittal and Detail Sheet.  
NOTE: Semi-recessed and surface-mounted cabinet compliance with ADA wall projection guidelines depends on several location and installation issues.  
Please refer to <http://www.larsensmfg.com/>



- DOOR DESIGN**

  - ☐ Vertical Letters
  - ☐ Horizontal Letters
  - ☐ Type A Letters
  - ☐ Clear - No Letters
  - ☐ Bronze - No Letters
  - ☐ Larsen-Loc®  
(Available with all door styles)
- DOOR & LETTERING COLORS**

  - ☐ Clear - No Letters
  - ☐ Clear - Red Letters
  - ☐ Clear - White Letters
  - ☐ Clear - Black Letters
  - ☐ White - Black Letters
  - ☐ White - Red Letters
  - ☐ Black - White Letters
  - ☐ Red - White Letters
  - ☐ Bronze - White Letters