Call Now ((718) 499-4881

SUBMITTAL: FIRE EXTINGUISHERS (9)*



PAGE 1 OF 2

All units meet the current requirements established by the National Fire Protection Association (NFPA) for NFPA10 (2010 version) "Standard for Portable Fire Extinguishers", and any other applicable NFPA standards. All units UL listed for US and Canada and meet local and national OSHA requirements for fire extinguishers.

GRENADIER EXTINGUISHERS - PRESSURIZED WATER

Pressurized Water Extinguishers for Class "A" Fires. The "water press" extinguisher contains water and compressed air. Units shipped empty. Operation: Squeeze the lever, which opens the valve, allowing the water to be forced out. Upright squeeze grip operation.

Construction: Butt-welded 304-L stainless steel cylinder (eliminates all internal and external crevices). Rugged stainless steel discharge lever and fixed carry handle with visual pressure gauge, pull pin. Heavy-duty, brass, chrome-plated valve body with replaceable molded valve stem seal. UL labeled chemical engine hose.

CLASS A Fires

COSMIC & 495 EXTINGUISHERS - MULTI PURPOSE CHEMICAL

These units contain specially fluidized and siliconized mono ammonium phosphate powder, which smothers and breaks the chain reaction on Class B fires, fuses and insulates Class A fires and is a non-conductor of electricity. Non-toxic.

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation approved to -65°F (-52°C).

Construction: Heavy-duty steel cylinder with rugged metal valve and siphon tube with replaceable molded valve stem seal, visual pressure gauge, pull pin and upright squeeze grip. Corrosion and impact-resistant powder coat finish.

CLASS A,B,C Fires

SENTINEL EXTINGUISHERS- CARBON DIOXIDE

This extinguisher contains liquid carbon dioxide under pressure.

Operation: Squeeze the lever, which opens the valve, allowing the carbon dioxide to be forced out. The discharge, which changes into a gas and appears as a smothering cloud of white snow, is then directed to the fire through a funnel-shaped horn. Electrically non-conductive. Construction: Lightweight, high-pressure, aluminum cylinder with O-ring seal and straight thread brass valve fits all sizes. The Sentinel is absolutely rust-free and up to 30% lighter than CO2 units with steel cylinders.

CLASS B,C Fires

272 - WATER MIST EXTINGUISHER

The water mist extinguisher is ideal for Class A fires where a potential Class C (electrical) hazard exists. Units shipped empty.

Operation: The unique misting nozzle provides safety from electrical shock, making this extinguisher ideal for use in telecommunications and cleanroom environments.

Construction: Non-magnetic cylinder and misting nozzle. For use in medical facilities. CLASS A,C Fires

GALAXY & 496 EXTINGUISHERS - REGULAR DRY CHEMICAL

These models contain a siliconized sodium bicarbonate base, the traditional dry chemical. Cleanup after use is generally easy, because the chemical does not normally bake to a hot metal surface. Non-toxic.

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Upright squeeze grip operation approved to -65°F (-52°C).

Construction: Heavy-duty steel cylinder with rugged metal valve and siphon tube with replaceable valve stem seal, visual pressure gauge pull pin and upright squeeze grip.

CLASS B,C Fires

MERCURY EXTINGUISHERS - HALOTRON AGENT

This model contains the clean extinguishing agent Halotron® 1, which is EPAapproved, government-accepted and specified. This agent discharges as a liquid, then quickly evaporates, leaving no residue to clean up afterwards. U.S. FAA-approved for use in airports. NFPA-10 rating. Electrically non-conductive.

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Temperature range from -40°F to +120°F.

Construction: Drawn steel cylinder with steel siphon tubes, power cone discharge stream, upright squeeze grip visual pressure gauge and corrosion-resistant paint finish. Models 2-1/2 & 5 have aluminum valves, models

CLASS A,B,C Fires

SATURN EXTINGUISHERS - CLASS K WET CHEMICAL

These units are ideal for commercial restaurant applications as a portable supplement to pre-engineered suppression systems. A low "pH" potassium acetate solution is discharged in a fine mist that provides excellent range while preventing splashing and creating an effective saponification foam-type blanket necessary for suppressing liquid cooking media fires.

Operation: Squeeze the lever, which opens the valve, allowing the chemical to be forced out. Construction: Stainless steel cylinder with protective nozzle tip orifice seal and non-metallic nozzle tip finger guard. Industry standard horn and nozzle design.

Name plate shows only the class "K" symbol. **CLASS K Fires**



CLASS A FIRES - PAPER, WOOD, CLOTH, ETC. WHERE QUENCHING BY WATER OR INSULATING BY DRY CHEMICAL IS EFFECTIVE.



CLASS B FIRES - PLAMMARLE LIQUIDS WHERE SMOTHERING ACTION IS REQUIRED.



CLASS C FIRES - LIVE ELECTRICAL EQUIPMENT WHERE THE NON-CONDUCTIVITY OF EXTINGUISHANT IS VITAL



CLASS K FIRES CALL JL INDUSTRIES FOR MORE INFORMATION

SUBMITTAL: FIRE EXTINGUISHERS

PAGE 2 OF 2

| Qty | Model | Nominal Capacity | Shipping Weight | Cylinder Diameter | Overall Height | Overall Width | Shipping Volume | UL Rating 👰 | Optional Mark Bracket | USCG Approved |
|-----|------------------------|------------------|-----------------|-------------------|----------------|---------------|-----------------|--------------|-----------------------|---------------|
| | Grenadier-P | 2-1/2 gal. | 7.75 lbs. « | 7* | 24-1/2* | 9" | 1.1 cu.ft. | 2A | MB810 | YES |
| | Cosmic 2-1/2E* | 2-1/2 lbs. | 5.5 lbs. | 3-3/8* | 15-1/2" | 5-3/4" | .2 cu.ft. | 1A-10BC | MB817C or MB817A* | YES |
| | Cosmic 5E | 5 lbs. | 10 lbs. | 4-1/4" | 16-3/8* | 7-1/4" | .35 cu.ft. | 3A-40BC | MB818C | YES |
| | Cosmic 6E | 6 lbs. | 12.75 lbs. | 5* | 16* | 7-3/4" | .5 cu.ft. | 3A-40BC | MB808A | YES |
| | Cosmic 10E | 10 lbs. | 18.25 lbs. | 5-1/8" | 21" | 7-3/4" | .65 cu.ft. | 4A-80BC | MB846C or MB846A | YES |
| | Cosmic 20E (FE20C) | 20 lbs. | 33.5 lbs. | 7-1/2" | 21-1/4" | 8-3/4" | 1.0 cu.ft. | 10A-120BC | MB811C | YES |
| | Cosmic 20E (FE20A) | 20 lbs. | 38 lbs. | 7* | 24" | 10-1/4" | 1.0 cu.ft. | 10A-120BC | MB810A | YES |
| | 495 | 50 lbs | 174 lbs | | 46" | 21-1/2" | | 20A-160BC | | |
| | Sentinel 5 | 5 lbs. | 14 lbs. | 5-1/4" | 17-3/4" | 8-1/4" | .65 cu.ft. | 5BC | MB809C or MB809A | YES |
| | Sentinel 10 | 10 lbs. | 28.25 lbs. | 7* | 24* | 12" | 1.3 cu.ft. | 10BC | MB810C or MB810A | YES |
| | Sentinel 15 | 15 lbs. | 37.75 lbs. | 7* | 30* | 12" | 1.0 cu.ft. | 10BC | MB810C or MB864A | YES |
| | Sentinel 20 | 20 lbs. | 50.75 lbs. | 8* | 30* | 13" | 2.1 cu.ft. | 10BC | MB811C or MB811A | YES |
| | Galaxy 2-1/2* | 2-1/2 lbs. | 5/5 lbs. | 3-3/8" | 15-1/2" | 5-3/4" | .2 cu.ft. | 10BC | MB817C or MB817A* | YES |
| | Galaxy 5 | 5 lbs. | 9.25 lbs. | 4-1/4" | 15-1/4" | 5-1/2* | .35 cu.ft. | 10BC | MB818A | YES |
| | Galaxy 5-1/2 | 5-1/2 lbs. | 10.5 lbs. | 4-1/4" | 16-3/8* | 7-1/4" | .4 cu.ft. | 40BC | MB818C or MB818A | YES |
| | Galaxy 6 | 6 lbs. | 13.75 lbs. | 5* | 16-1/4" | 8-1/2* | .5 cu.ft | 40BC | MB808A | YES |
| | Galaxy 10 | 10 lbs. | 18.25 lbs. | 5-1/8" | 21* | 7-3/4" | .65 cu.ft. | 40BC or 60BC | MB846C or MB846A | YES |
| | Galaxy 20 | 20 lbs. | 38 lbs. | 7-1/2" | 23-1/4" | 10-1/4" | 1.0 cu.ft. | 120BC | MB810C or MB810A | YES |
| | 496 | 50 lbs. | 174 lbs. | | 46" | 21-1/2" | | 160BC | - | |
| | Mercury 2-1/2* | 2-1/2 lbs | 5.25 lbs | 3-3/8" | 15-1/2* | 6-3/8" | .25 cu.ft. | 2BC | MB817C or MB817A* | N/A |
| | Mercury 5 | 5 lbs | 9.5 lbs | 4-1/4" | 16-3/8* | 7-1/4" | .3 cu.ft. | 5BC | MB818C or MB818A | YES |
| | Mercury 11 (FM11C) | 11 lbs | 21.25 lbs | 7" | 17-1/2" | 8-5/8" | 1.0 cu.ft. | 1A-10BC | MB810C | YES |
| | Mercury 11 (FM11A) | 11 lbs | 22.5 lbs | 6" | 21-7/8" | 9-1/4" | 1.0 cu.ft. | 1A-10BC | MB812A | YES |
| | Mercury 15-1/2 (FM15C) | 15-1/2 lbs | 25.75 lbs | 7* | 17-1/2" | 8-5/8" | 1.0 cu.ft. | 2A-10BC | MB810C | YES |
| | Mercury 15-1/2 (FM15A) | 15-1/2 lbs | 27.5 lbs | 6" | 21-7/8* | 9-1/4" | 1.0 cu.ft. | 2A-10BC | MB812A | YES |
| | Saturn 15 | 1.8 gal | 22.5 lbs | 7* | 19-1/4" | 9* | .9 cu.ft. | Class K | MB810C or MB810A | - |
| | Saturn 25 | 2.5 gal | 33.5 lbs. | 7* | 24-1/2* | 9* | 1.1 cu.ft. | Class K | MB810C or MB810A | - |
| | 272 | 2.5 gal | 8 lbs. «c | 7* | 28" | 14" | 1.3 cu ft. | 2AC | MB810NM | |

INDICATES MARK BRACKET STANDARD. J HOOK WALL BRACKET STANDARD WITH ALL OTHER EXTINGUISHERS.

«JL extinguishers are shipped fully charged with the exception of the Grenadier P & 272. Note: NFPA regulations also require extinguishers to be inspected when initially placed in service and all local fire code and tagging requirements must be adhered to. All fire extinguisher sizes are nominal. Contact Customer Service For More Information About Ordering Tagged Extinguishers in Your Area.